

11:28

14:28

15:28

22:28

HAWAII

GUAM

JAPAN

ZULU

SPECIFICATIONS

BTZ-42425-4

- TYPE: ----- DIGITAL
- DISPLAY: ----- 4-DIGIT, 7 SEGMENT RED SUPER BRIGHT LED
- CHARACTER HEIGHT: ----- 2.5" (63.5 mm) HR./MIN.
- VISIBILITY: ----- 100 Ft. (30.48 METERS)
- POWER REQUIREMENTS: 100-240V 50~60Hz (12vdc SWITCHING POWER SUPPLY)
- FRAME: ----- ALUMINUM (BLACK ANODIZED FINISH)
- DIMENSIONS: ----- 7.25" x 55.25" x 1.375"
- WEIGHT: ----- 8 lbs.
- OPERATING TEMP.: ----- -17° TO 190° F
- HUMIDITY: ----- 0% TO 95% NON-CONDENSING
- OPERATING MODE: ----- SYNCHRONIZED ZONES WITH ONE MASTER SET ZONE.




ALL CLOCKS USE THE DALLAS DS3231 RTC PARTS, AND OUR FIRMWARE CONTROL, TO GET THE ONE SEC A YEAR ACCURACY. **1 SEC A YEAR ACCURATE (TCXO)**

World's Most Accurate RTC



- 1.8", 2.5" and 4" DIGIT SIZE
- 12 OR 24 HOUR FORMAT
- 2 TO 24 ZONES
- NON GLARE LENS
- SUPER BRIGHT LEDS
- CUSTOM LETTERING TO YOUR SPECIFICATION
- ALUMINUM FRAME SURFACE MOUNT OR FLUSH
- 10 YEAR LITHIUM BATTERY BACKUP (Standard)
- AUTOMATIC DAY LIGHT CORRECTION (Standard)
- INFRARED REMOTE CONTROL (Standard)
- ONE SEC A YEAR ACCURACY (TCXO) (Standard)



MOUNTING INSTRUCTIONS

