

11:28

LOCAL

14:28

ZULU

15:28

ELMENDORF


BTZ-42440-3

SPECIFICATIONS

TYPE: -----	DIGITAL
DISPLAY: -----	4-DIGIT, 7 SEGMENT RED SUPER BRIGHT LED
CHARACTER HEIGHT: -----	4" (101.6 mm) HR. MIN.
VISIBILITY: -----	250 Ft. (76.2 METERS)
POWER REQUIREMENTS:--	110-240V 50~60Hz (12vdc Switching Power Supply)
FRAME: -----	ALUMINUM (BLACK ANODIZED FINISH)
DIMENSIONS: -----	10.25" x 48.25" x 1.5"
WEIGHT: -----	6.8. lbs.
OPERATING TEMP.: -----	-17° TO 182° F
HUMIDITY: -----	0% TO 95% NON-CONDENSING
OPERATING MODE:-----	IRR CONTROL and SYNCHRONIZED ZONES



- 1.8", 2.5" and 4" DIGIT SIZE
- 12 OR 24 HOUR FORMAT
- 2 TO 24 ZONES
- NON GLARE LENS
- SUPER BRIGHT LEDs
- CUSTOM LETTERING TO YOUR SPECIFICATION
- BLACK ANODIZED ALUMINUM FRAME
- 10 YEAR LITHIUM BATTERY BACKUP (Standard)
- AUTOMATIC DAY LIGHT CORRECTION (Standard)
- INFRARED REMOTE CONTROL (Standard)
- ONE SEC A YEAR ACCURACY (TCXO) (Standard)



ALL CLOCKS USE THE DALLAS DS32 SERIES RTC PARTS, AND OUR FIRMWARE CONTROL, TO GET THE ONE SEC A YEAR ACCURACY.

World's Most Accurate RTC

1 SEC A YEAR ACCURATE (TCXO)

