11:28 14:28 15:28

LOS ANGELES

OHIO

JAPAN

BTZ-42418-3



SPECIFICATIONS

DIGITAL

4-DIGIT, 7 SEGMENT RED SUPER BRIGHT LED DISPLAY: -----

CHARACTER HEIGHT: ----- 1.8" (45.72 mm)

VISIBILITY: ----- 75 Ft. (22.86 MÉTERS)

POWER REQUIREMENTS:--- 100-240V 50~60Hz (12vdc Switching Power Supply)

FRAME: ----- ALUMINUM (BLACK ANODIZED FINISH)

DIMENSIONS: ----- 6.25" x 36.25" x 1.38"

WEIGHT: ----- 4.5 lbs.

OPERATING TEMP.: ----- -17° TO 180° F

HUMIDITY: ----- 0% TO 95% NON-CONDENSING

OPERATING MODE:----- IRR REMOTE WITH SYNCHRONIZED ZONES



1.8", 2.5" and 4" DIGIT SIZE 12 OR 24 HOUR FORMAT 2 TO 24 ZONES NON GLARE LENS SUPER BRIGHT LEDS

CUSTOM LETTERING TO YOUR SPECIFICATION BLACK ANODIZED ALUMINUM FRAME

10 YEAR LITHIUM BATTERY BACKUP (Standard) AUTOMATIC DAY LIGHT CORRECTION (Standard) INFRARED REMOTE CONTROL (Standard) ONE SEC A YEAR ACCURACY (TCXO) (Standard)

ALL CLOCKS USE THE DALLAS DS32 SERIES RTC PARTS, AND OUR FIRMWARE CONTROL, TO GET THE ONE SEC A YEAR ACCURACY.



1 SEC A YEAR ACCURATE (TCXO)

