



SPECIFICATIONS

BTZ- 42425-3

- TYPE: ----- DIGITAL
- DISPLAY: ----- 4-DIGIT, 7 SEGMENT RED SUPER BRIGHT LED
- CHARACTER HEIGHT: ----- 2.5"(63.5 mm) HR./MIN.
- VISIBILITY: ----- 150 Ft. (45.72 METERS)
- POWER REQUIREMENTS: 100-240V 50~60 Hz (*12vdc Switching Supplay*)
- FRAME: ----- ALUMINUM (BLACK ANODIZED FINISH)
- DIMENSIONS: ----- 7.25" x 38.25" x 1.375"
- WEIGHT: ----- 6.5 lbs.
- OPERATING TEMP.: ----- -17° TO 190° F
- HUMIDITY: ----- 0% TO 95% NON-CONDENSING
- OPERATING MODE: ----- SYNCHRONIZED ZONES WITH ONE MASTER SET ZONE.



ALL CLOCKS USE THE DALLAS DS32 SERIES RTC PARTS, AND OUR FIRMWARE CONTROL, TO GET THE ONE SEC A YEAR ACCURACY. **World's Most Accurate RTC**
1 SEC A YEAR ACCURATE (TCXO)

- 1.8", 2.5" and 4" DIGIT SIZE
- 12 OR 24 HOUR FORMAT
- 2 TO 24 ZONES
- NON GLARE LENS
- SUPER BRIGHT LEDS
- CUSTOM LETTERING TO YOUR SPECIFICATION
- ALUMINUM FRAME SURFACE MOUNT OR FLUSH
- 10 YEAR LITHIUM BATTERY BACKUP (*Standard*)
- AUTOMATIC DAY LIGHT CORRECTION (*Standard*)
- INFRARED REMOTE CONTROL (*Standard*)
- ONE SEC A YEAR ACCURACY (TCXO) (*Standard*)

