

11:28

LOCAL

14:28

ZULU

15:28

ELMENDORF


BTZ-42440-3

SPECIFICATIONS

- TYPE: ----- DIGITAL
- DISPLAY: ----- 4-DIGIT, 7 SEGMENT RED SUPER BRIGHT LED
- CHARACTER HEIGHT: ----- 4" (101.6 mm) HR. MIN.
- VISIBILITY: ----- 250 Ft. (76.2 METERS)
- POWER REQUIREMENTS:-- 110-240V 50~60Hz (**12vdc Switching Power Supply**)
- FRAME: ----- ALUMINUM (BLACK ANODIZED FINISH)
- DIMENSIONS: ----- 10.25" x 48.25" x 1.5"
- WEIGHT: ----- 6.8. lbs.
- OPERATING TEMP.: ----- -17° TO 182° F
- HUMIDITY: ----- 0% TO 95% NON-CONDENSING
- OPERATING MODE:----- IRR CONTROL and SYNCHRONIZED ZONES



- 1.8", 2.5" and 4" DIGIT SIZE
- 12 OR 24 HOUR FORMAT
- 2 TO 24 ZONES
- NON GLARE LENS
- SUPER BRIGHT LEDS
- CUSTOM LETTERING TO YOUR SPECIFICATION
- BLACK ANODIZED ALUMINUM FRAME
- 10 YEAR LITHIUM BATTERY BACKUP (**Standard**)
- AUTOMATIC DAY LIGHT CORRECTION (**Standard**)
- INFRARED REMOTE CONTROL (**Standard**)
- ONE SEC A YEAR ACCURACY (TCXO) (**Standard**)



ALL CLOCKS USE THE DALLAS DS32 SERIES RTC PARTS, AND OUR FIRMWARE CONTROL, TO GET THE ONE SEC A YEAR ACCURACY.

World's Most Accurate RTC

1 SEC A YEAR ACCURATE (TCXO)



MOUNTING INSTRUCTIONS

